

Monsher Hydrant Valves

MONSHER
(INDIA) SAFETY EQUIPMENTS PVT. LTD.
We perform. You deliver.




Turn on safety, whenever you want.

Monsher India Safety Equipments is proud to present the nation's leading single and double valve fire hydrants.

Manufactured with the best materials and made to the highest standards, these are the hydrants to turn to when you want safety delivered.

DOUBLE CONTROLLED HYDRANT VALVE



FLANGE DIMENSION:-


FLANGE	PCD	HOLES	HOLES
220 MM	180	8	19 MM

NO.	ITEM DESCRIPTION	MATERIAL SPECIFICATION
1	BODY	IGM
2	SPINDLE	BRASS
3	BONNET	LTB-2.
4	GLAND BUSH	LTB-2.
5	GLAND PACKING	ASBESTOSE ROPE
6	GLAND NUT	LTB-2.
7	CHECK NUT (SPINDLE)	LTB-2.
8	SEAT WASHER	RUBBER
9	STOP VALVE	LTB-2.
10	SEAT CHECK NUT	LTB-2.
11	HEX. NUT	M.S.
12	HAND WHEEL	C.I.
13	FEMALE OUTLET	LTB-2.
14	LOWER LUG	LTB-2.
15	UPPER LUG	LTB-2.
16	BLANK CAP	G.M. / P.V.C.
17	RUBBER RING	RUBBER
18	CHAIN	GALVANISED

TECHNICAL DATA SHEET

Description	63mm Double Controlled Hydrant Valve Type B.	Data Sheet No.	MON/HYD/002
Reference Standard	Type B	Size :	63mm
Material Specification			
Part List	Material of Construction		
Body	GM / CI		
Spindle	Brass / SS		
Spring	Phosphor Bronze Wire / SS Wire		
Hand Wheel	C.I.		
Washer	Rubber		
Connection			
Flange Inlet	100mm NB		
Female Inst. Outlet	63mm Female Inst. Adaptor		
Inspection & Testing			
Hydrostatic Test Pressure			
• Water Tightness	14 kgf/cm ²		
• Body	21 kgf/cm ²		
Flow Test	1800 LPM Min at 7 kgf/cm ²		
Manufacturers Test Certificate	Yes		
Finish			
Body	Painted by Fire Red Colour		
Wheel	Painted by Black Paint		
Parts	Polished		
Marking			
Brand Name	MONSHER		
Size	63mm		
Year	Year of Manufacturing		
Warranty & Guarantee	12 Months from the date of supply		

OBLIQUE TYPE HYDRANT VALVE



FLANGE DIMENSION:-

FLANGE	PCD	HOLES	HOLES
200 MM	160	4	19 MM

NO.	ITEM DESCRIPTION	MATERIAL SPECIFICATION
		GUN METAL
1	BODY	G.M.
2	SPINDLE	Brass
3	BONNET	G. M.
4	GLAND BUSH	Brass
5	GLAND PACKING	ASBESTOSE ROPE
6	GLAND NUT	Brass
7	CHECK NUT (SPINDLE)	Brass
8	SEAT WASHER	RUBBER IS:937
9	STOP VALVE	Brass
10	SEAT CHECK NUT	Brass
11	HEX. NUT	M.S.
12	HAND WHEEL	C.I.
13	FEMALE OUTLET	G. M.
14	LOWER LUG	G. M.
15	UPPER LUG	G. M.
16	BLANK CAP	ABS
17	RUBBER RING	RUBBER IS:937
18	CAM TOOTH	Brass
19	CHAIN	GALVANISED

TECHNICAL DATA SHEET

Description	63mm Oblique Type Fire Hydrant Valve having 65mm NB Flanged Inlet	Data Sheet No.	MON/HYD/001
Reference Standard	Type -A	Size :	63mm
Material Specification			
Part List	Material of Construction		
Body	GM/S5		
Spindle	BRASS		
Spring	Phosphor Bronze Wire / SS Wire		
Hand Wheel	C.I.		
Washer	Rubber		
Connection			
Flange Inlet	65mm NB		
Female Inst. Outlet	63mm Female Inst. Adaptor		
Inspection & Testing			
Hydrostatic Test Pressure			
• Water Tightness	14 kgf/cm ²		
• Body	21 kgf/cm ²		
Flow Test	900 LPM Min at 7 kgf/cm ²		
Manufacturers Test Certificate	Yes		
Finish			
Body	Painted by Fire Red Colour		
Wheel	Painted by Black Paint		
Parts	Polished		
Marking			
Brand Name	MONSHER		
Size	63mm		
Year	Year of Manufacturing		
Warranty & Guarantee	12 Months from the date of supply		