



We're giving safety a new canvas.

Special Features

- The Rack Hose-FAS is an all polyester single jacket interior protection hose perfect for buildings and plants. The Rack Hose-FAS is thicker than Rack Hose-FBS.
- It has high working pressures, is economical and easy to handle
- Its cover is resistant to weather, ozone, oxidation, and UV, as well as most chemicals and petroleum products.
- The rack hose is available folded for standard pin racks in 50' (15m), 75' (22.5m), and 100' (30m) lengths. You can specify folded, coiled, or number of pins for rack

Pressure Requirement

I. D. (Inch/mm)		Working Pressure (Bar/Psl)			Burst Pressure (Bar/Psl)
1"	25	10/150	14/200	17/250	31/450, 42/600, 51/750
1 1/2"	38	10/150	14/200	17/250	31/450, 42/600, 51/750
1 3/4"	45	10/150	14/200	17/250	31/450, 42/600, 51/750
2 1/2"	65	10/150	14/200	17/250	31/450, 42/600, 51/750

Application

Building Protection
Wash Down

Couplings Available

Aluminum & Brass NH/NST or IPT, Aluminum Storz, Instantaneous coupling etc.

Colour

The standard colour for Sharp Rack Hose-FAS is white. Other colours available with our innovative Wisentec abrasion resistant coatings are red, yellow, orange, blue, green and tan. The colours provide water repellency, abrasion, oil and chemical resistance. Colours are uniform throughout the length of each hose. Colour coating costs additional.

Construction

Polyester spun as warp and filament polyester as weft, E.P.D.M. inner liner.

Standards

Our fire hoses manufactured to this specification meet and exceed all performance requirements of NFPA 1961, Underwriter's Laboratories & Factory Mutual.

